



ACCESS CONTROL

CAFETERIA
MANAGEMENT

TIME-ATTENDANCE

COSEC DOOR FOP V3

Optical Fingerprint and Card Based Door Controller

JOB PROCESSING
AND COSTING

VEHICLE ACCESS MANAGEMENT



VISITOR MANAGEMENT

CONTRACT WORKERS
MANAGEMENTproduct
design
awardGOOD
DESIGN

INDIA DESIGN MARK

GENERAL

Credential Support

Fingerprint, RFID Card and PIN
Proximity (EM Prox, HID Prox) and

RF Option

Smart Cards (Mifare, NFC Tag and HID iCLASS)
(COSEC CPM Module Required)

CAPACITY

Max. Users

50,000

Max. Template Storage

9,600 in 1: N Mode and 100,000 in 1:1 Mode

Event Buffer

500,000

Templates per User

Up to 10 (Single Template per Finger Mode)

Up to 5 (Dual Template per Finger Mode)

Cards per User

Up to 2

COMMUNICATION

Ethernet

Yes (10/100 Mbps)

RS-232

Yes

Mobile Broadband

Yes

Wiegand

Wiegand IN Available

USB

2 USB Port (Data Transfer and 2G-3G Dongle)

INTERFACE

Exit Switch

Yes

Door Status Sense

Programmable NO, NC, Supervised

Door Lock Relay

30V DC @ 1 A, Form C, SPDT Relay

Door Lock Power

Internal 12V DC @ 0.5A or External

Aux-In

Programmable NO, NC, Supervised

Aux-Out

30V DC @ 1 A, Form C, SPDT Relay

Reader Interface Types

RS-232, and Wiegand IN

HARDWARE

CPU

400 MHz ARM 9 Based Processor

Memory

256 MB Flash + 128 MB DDR3 RAM

Display

128 x 64 Dot Matrix Display

Display Size

38.1mm x 60.96mm (1.5" x 2.4")

LED

4 LED (Status, Alarm, Allowed, Denied)

Buzzer	Yes
Keypad	16 Touch Sense Keys
Operating Temperature	0°C to +45°C (32°F to 113°F)
Humidity	5% to 85% RH Non - Condensing
Tamper Detection	Yes
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to Lock from COSEC DOOR FOP) 30V DC @1 A (Power to lock from External Adaptor)
Dimensions (W x H x D)	100mm x 220mm x 56mm (3.93"x 8.66"x 2.20")
Weight	0.65 Kgs (1.43 lbs.)

COMPATIBILITY

System Integration	API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA Server Panel Door with COSEC PANEL LITE V2

SENSOR

Sensor Name	Suprema Sensor
Sensor Technology	Optical Sensing
Encryption	256-bit AES
Water-proof	Yes
False Acceptance Ratio (FAR)	0.001%
False Rejection Ratio (FRR)	0.01%
Resolution (dpi)	500 dpi
Sensing Area	16.0mm x 19.0mm
Template Size	256 ~ 384 bytes (Configurable, 384 bytes default)
Image Size (Pixel)	272mm x 320mm

APPLICATIONS

Access Control
Time-Attendance
Visitor Management
Contract Workers' Management
Cafeteria Management
Job Processing and Costing

**Due to continuous technology upgradations, product specifications are subject to change without notice.*

ABOUT MATRIX

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.



SECURITY SOLUTIONS

MATRIX COMSEC

Head Office

394-GIDC, Makarpura, Vadodara-390 010,
India.

Ph: +91 265 2630555

E-mail: Inquiry@MatrixComSec.com

Factory

19-GIDC, Waghodia, Dist. Vadodara-391 760,
India.

Ph: +91 2668 263172/73

www.MatrixAccessControl.com